

Perforated plate

Perforated plate



Plaque perforée

Description

- Galvanised steel S250GD+Z275 in accordance with NF EN 10346.
- Steel thickness: 2 mm

Product benefits

- Multiple applications
- Ideal for end-to-end joining when connecting posts to beams

Uses

SUBSTRATES:

- Supporting member: solid wood, composite wood, glued laminated timber.
- Supported member: solid wood, composite wood, glued laminated timber, concrete, hollow masonry.

APPLICATIONS:

- End-to-end joining, repairs, post-to-beam connection etc.

Homologations




CE
NF EN 14545

Materials



Wood



Plaque perforée - en situation

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDIT	HEIGHT	WIDTH	THICKNESS
PLAQUE PERFOREE 40 X 120 X 2 Bte de 100	A472060	Boîte de 100	120 mm	40 mm	2 mm
PLAQUE PERFOREE 40 X 160 X 2 Bte de 100	A472065	Boîte de 100	160 mm	40 mm	2 mm
PLAQUE PERFOREE 60 X 160 X 2 Bte de 50	A472080	Boîte de 50	160 mm	60 mm	2 mm
PLAQUE PERFOREE 60 X 200 X 2 Bte de 50	A472100	Boîte de 50	200 mm	60 mm	2 mm
PLAQUE PERFOREE 80 X 200 X 2 Bte de 50	A472120	Boîte de 50	200 mm	80 mm	2 mm
PLAQUE PERFOREE 80 X 240 X 2 Bte de 50	A472140	Boîte de 50	240 mm	80 mm	2 mm

DÉSIGNATION	RÉFÉRENCE	CONDT	HEIGHT	WIDTH	THICKNESS
PLAQUE PERFOREE 100 X 200 X 2 Bte de 50	A472160	Boîte de 50	200 mm	100 mm	2 mm
PLAQUE PERFOREE 100 X 300 X 2 Bte de 50	A472170	Boîte de 50	300 mm	100 mm	2 mm