

## Beam clamp

### Beam clamp with unthreaded through hole for metal beams



Agrip-tige

#### Description

- Beam clamp with unthreaded through hole for metal beams.
- White zinc plating.
- M6 beam clamp:
  - unthreaded through hole Ø7 for M6 threaded rod
  - Grip height: 18 mm
- M8 beam clamp:
  - unthreaded through hole Ø9 for M8 threaded rod
  - Grip height: 18 mm
- M10 beam clamp:
  - unthreaded through hole Ø11 for M10 threaded rod
  - Grip height: 20 mm
- M12 beam clamp:
  - unthreaded through hole Ø13 for M12 threaded rod
  - Grip height: 26 mm

#### Product benefits

- For suspending metal beams.



Agrip-tige - vue en situation

#### Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	DIAMETER	FINITION
AGRIP TIGE M6 Bte de 20	A180020	Boîte de 20	Trou lisse Ø6 mm	Zinguée blanche
AGRIP TIGE M8 Bte de 20	A180021	Boîte de 20	Trou lisse Ø8 mm	Zinguée blanche
AGRIP TIGE M10 Bte de 20	A180022	Boîte de 20	Trou lisse Ø10 mm	Zinguée blanche
AGRIP TIGE M12 Bte de 20	A180023	Boîte de 20	Trou lisse Ø12 mm	Zinguée blanche

#### Technical informations - average indicative loads (en kg)

120

120

250

350