

Anchor bushing with internal cone Metal anchor for supporting a threaded rod



Chevilles cône intérieur

Description

- Metal anchor for supporting a threaded rod.
- Compatible with metric screws and threaded rods.

Product benefits

- Minimal anchorage depth: can be anchored in a narrower substrate.
- Controlled expansion thanks to setting tool.
- Fire-resistant.

Uses

- Fixing and support for threaded rod in concrete and solid materials – even narrower substrates.

Homologations



ETA 14-0339.

Materials



Concrete



Solid breeze block /
Stone



Solid
brick



Chevilles cône intérieur - outil de
pose

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT	LENGTH	THREAD
CHEVILLE CONE INTERIEUR M 6 Bte de 200	A260310	Boîte de 200	Aucun	25 mm	M6
CHEVILLE CONE INTERIEUR M 8 Bte de 100	A260320	Boîte de 100	Aucun	30 mm	M8
OUTIL DE POSE M 6 Sachet de 1	A260230	Sachet de 1	Aucun	-	M6
OUTIL DE POSE M 8 Sachet de 1	A260240	Sachet de 1	Aucun	-	M8

Technical informations - Implementation data

	ANCHOR LENGTH	THREAD LENGTH	DRILLING DIAMETER	DRILLING DEPTH
M6	25 mm	12 mm	8 mm	30 mm

	ANCHOR LENGTH	THREAD LENGTH	DRILLING DIAMETER	DRILLING DEPTH
M8	30 mm	14 mm	10 mm	35 mm

Technical informations - Average indicative loads (kg)

	M6	M8
CONCRETE	130	230
STONE / SOLID BREEZE BLOCK	115	205
SOLID BRICK	115	205

Technical informations - Utilisation

