

Rapido®

Threaded rod hanger for use directly in concrete



Rapido

Description

- Threaded rod hanger for use directly in concrete.
- Available in M6, M7 and M8 versions.
- Setting tool: Hex socket, 10 mm.
- Driver adjustment: high torque/low speed.
- Not to be used with an impact wrench.
- Permissible load: 100 kg (factored load with a safety coefficient of 3).




Concrete

Product benefits

- No wall plug required: quick and economical installation.
- Reduced drilling diameter 6 mm : time savings.
- Patented.

Uses

- Plasterboard ceilings, light fittings, cable trays, suspended ceilings, sanitary pipe clamps, heavy-duty pipe clamps, air-conditioning units, mechanical controlled ventilation etc.



Rapido - Vue en coupe



Rapido - Vue en situation



Rapido M6 - vue en situation



Rapido M7 - vue en situation



Rapido M8 - vue en situation

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT	THREAD	DRILLING
RAPIDO DIRECT BÉTON M6 Bte de 100	A188090	Boîte de 100	Aucun	M6	Ø 6 mm
RAPIDO DIRECT BÉTON M7X150 Bte de 100	A188100	Boîte de 100	Aucun	M7	Ø 6 mm
RAPIDO DIRECT BÉTON M8 Bte de 100	A188150	Boîte de 100	Aucun	M8	Ø 6 mm
RAPIDO DIRECT BÉTON M6 Sachet de 20	A853350	Sachet de 20	20 sachets	M6	Ø 6 mm
RAPIDO DIRECT BÉTON M7X150 Sachet de 20	A853355	Sachet de 20	20 sachets	M7	Ø 6 mm
RAPIDO DIRECT BÉTON M8 Sachet de 20	A853360	Sachet de 20	20 sachets	M8	Ø 6 mm
OUTIL RAPIDO L'unité	A270345	Unité	Aucun	-	-

Small diameter drilling
Time savings



Driver adjustment: high torque/low speed

Not to be used with an impact wrench