

SPEEDY-FIX®

Hanger for use directly in concrete

**SPEEDY-FIX**

Description

- Hanger for use directly in concrete.
- Setting tool supplied.
- Drill hole Ø 5 mm.
- Driver adjustment: high torque/low speed.
- Not to be used with an impact wrench.
- Permissible load: 100 kg (factored load with a safety coefficient of 3).
- Thread length: 32 mm.
- Total length : 68 mm.
- Eyelet diameter: 5.5 mm.



Concrete

Product benefits

- No wall plug required: quick and economical installation.
- Reduced drilling diameter (Ø5): time savings.
- Made in France.

Uses

- Can be used to suspend chains, steel wires, hooks, carabiners, cables, unthreaded rods, cable trays etc.

**SPEEDY-FIX - vue en coupe****SPEEDY-FIX - vue en situation****SPEEDY-FIX - vue en situation**

Références produits

DÉSIGNATION	RÉFÉRENCE	CONDT	SURCONDT	DRILLING
SPEEDY-FIX Seau de 200	A270348	Seau de 200	Aucun	Ø 5 mm
SPEEDY-FIX Bte de 100	A270350	Boîte de 100	Aucun	Ø 5 mm
SPEEDY-FIX Sachet 25	A858845	Sachet de 25	10 Sachets	Ø 5 mm
SPEEDY-FIX Sachet de 50	A858850	Sachet de 50	10 Sachets	Ø 5 mm

Technical informations - Installation

